

Wind Speed Sensor

AT-FST200—201 Wind Speed Sensor

Features

- Excellent resistance against impact, overload, shock and erosion
- Small and exquisite, easy to take, simple to install
- Alloy material finish, reasonable structure design and nice outlook quality
- Stainless steel Wind cup, anti-wind load can reach 70m/s

Applicable Scope

- Working aloft testing and control
- Engineering machine testing and control
- Weather station and environment protection testing and control
- Port and wharf environment testing and control
- Other industrial automation about wind speed and direction testing and control




Project

Parameter

Technical Index	Output	Pulse signal (HZ)	0-5VDC	4-20mA
	Working Voltage	5VDC 24VDC	12~36VDC(common 24VDC)	
	Testing range	0.5m/s~50m/s		
	Start wind speed	≤0.5m/s		
	Accuracy	± 0.5m/s(<5m/s)		
		± 3% FS(≥5m/s)		
	Working Environment	Temperature: -20℃~+85℃ Humidity≤95% RH		
	Limit wind speed	Max: 70m/s 30min		
	Electrical connection	M12		
Environmental Protection	IP65			

Dimension



M12 Connection	Potential Lead	Output Signal	Serial NO	Wiring Method	
	3-Wire	Current mode	1	+Vcc	Brown
			2	+Vout	White
			3	GND	Blue
			4	PE	Black
	3-Wire	Voltage mode	1	+Vcc	Brown
			2	+Vout	White
			3	GND	Blue
			4	PE	Black
	3-Wire	Pulse mode	1	+Vcc	Brown
			2	+P ovt	White
			3	GND	Blue
			4	PE	Black



Your distributor
Hitma B.V.
hitma-instrumentatie.nl
+31(0)297-514 833

